

# Knit Pro Wallet

## Supplies :

- Fabric for the external cover : 12.2 in x 22 in
- Fabric for internal pages : 4 rectangles of 12.2 in x 20.5 in
- Fabric for inside pouches (according to your needs, please refer below to the size of pouches) : the fabric is stiched double
- Jeffitex or rigid material for better holding: 2 rectangles of 12.2 in x 10.2 in and 3 rectangles of 12.2 in x 9.8 in
- 1 full zip closure of 7 in
- 2 buttons pressures diameter 0.4 in
- Elastic about 15.7 in wide by 0.6 in
- 28.3 in of cloth tape to close your KPW
- 15.7 in of thin ribbon to tie your spanner (it is duplicate in order to hold the key)

## Size of inside pouches make sure to use double-layered fabric :

- 2 pockets for interchangeable needles : 3 in x 8.3 in
- 2 pockets for fixed circular needles : 5.5 in x 6.7 in
- 1 pocket for cable terminals (with full zip closure) : 4 in x 8.3 in
- 1 pocket for needle gauge : 2 .4 in x 4 in
- 1 pocket for needle huggers : 2.8 in x 3 in + flap 1.2 in x 3.5 in
- 1 pocket for cable needles + scissors : 2 in x 3.5 in
- 1 pocket for tape measure : 3.5 in x 2.6 in
- 1 pocket for stich markers : 3 in x 3.3 in + flap : 1.2 in x 3.5 in
- 1 pocket for hooks : 3 in x 6.7 in.

## Cable-ties in rubber bands :

- 2 cables : 1.4 in
- 3 cables : 1.8 in
- 5 cables : 2.6 in

Circular needles ties 30 cm : 12 in length X 4 times

### Confection :

The Knit Pro Wallet (KPW) is like a kind of book with several pages. I will therefore refer to the cover and to the internal pages.

The back of the cover is not stiffened to allow more flexible use, but you can top it up, if you prefer something really stiffer.

To begin, sew all pouches on the different inside pages. Each page measures 9.8 in in wide by 12.2 in high. There are 0.8 in between the left side and the right side to give ease of movement when the pocket is filled.

The interiors are in the same fabric as that used for the cover, but it is folded in 2, the fold is sewn and positioned upwardly. Hems are are angled inwards so that nothing comes to bother the storage.

Their position on different pages :

**Cables page:** position of rubber-bands you will beforehand have covered with the fabric:

Positions are given from the top to the bottom and from the left to the right :

- 5 cables (24,32,40,48,60) : 0.4 in from top and 3.5 in from the left for the upper position and 2.4 in from top and 4.8 in from left for the bottom position.
- 3 cables (16,24,32) : 5.5 in from top and 6.7 in from the left for the upper position and 6.3 in from top and 8 in from the left for the bottom position.
- 3 cables (16,24,32) : 8 in from top and 4.5 in from the left for the upper position and 9.5 in from top and 4.5 in from the left for the bottom position.
- 3 cables (60,48,40) : 9 in from top and 0.6 in from the left horizontally.

- 2 cables (40, 48/60) : 9 in from top and 7 in from the left for the upper position and 10 in from top and 7.5 in from the left for the bottom position.

### Circular needles 12 in :

- 4 in from top and 2 in from the left for the upper position and 5 in from top and 1 in from the left for the bottom position
- 3.5 in from top and 4 in from the left for the upper position and 4 in from top and 5.5 in from the left for the bottom position
- 9.5 in from top and 5 in from the left for the upper position and 11 in from top and 3.5 in from the left for the bottom position
- 8.5 in from top and 6.5 in from the left horizontally

for the other pages, position your different pockets according to your equipment, or grab yourself a few ideas from mine.

Do not forget to sew thin ribbon with the spanner in the middle of the cables pages and interchangeable needles pages.

When your inside pages task will be done, you will then obtain 4 big pieces, each of them divided in 2 pages. It will give you then 8 pages. We will paginate them from 1 to 8 in order to identify clearly each page.

Set together right sides pages 2 and 3. Sew together the 3 outside edges. Turn your project over to the right side and slide into the jeffitex. Sew together the internal edges (I mean the 4th side) along the jeffitex in order to hold it

Use the same procedure with pages 4 and 5 , pages 6 and 7.

Then take the cover. Position the jeffitex over, both ribbons for the closing, then pages 1 and 8 of the internal side. Fold hems inwards and sew on 4 sides of the front and do the same thing for the back.

Finish by sewings on top and in the bottom of the middle. Personaly I have done it by hand because it was not obvious to place the machine in the right way, but I am not an expert !